



1. WHERE WALLS JAIL UP TO GRID, LOCATE FACE OF STUD OR FACE OF CONCRETE AT GRID, U.N.O.
2. FINISH FLOOR ELEVATION TYPICAL ACROSS LEVEL, U.N.O.
3. REFER TO 10.0 AND 11.0 FOR ASSEMBLIES.
4. ATTENDING WORKERS ARE TO BE TRAINED AND CENTERLINE OF CONCRETE COLUMN, U.N.O.
5. T.O. CURBS & A/F. MAXIMUM A/F. WHERE SLAB IS SLOPED, U.N.O.
6. MIN. 1% SLOPE TO DRAINAGE NECESSARY.
7. TOP OF CONCRETE SLAB ELEVATIONS PROVIDED FOR REFERENCE. CONTRACTOR SHALL COORDINATE WITH FINISH ELEVATIONS PROVIDED ON ARCHITECTURAL PLANS AND ADJUST ELEVATIONS AS NECESSARY.
8. CEILING HEIGHTS MEASURED FROM TOP OF CONCRETE - SEE SECTIONS.
9. COORDINATE WITH ALL ENLARGED PLANS FOR ADDITIONAL INFORMATION AND DETAILS.
10. COORDINATE WITH ELECTRICAL PLANS FOR ALL ELECTRICAL AND PLUMBING FIXTURE DETAILS, AND REINFORCING FOR COLUMNS, BEAMS, SHEAR WALLS, ETC.
11. COORDINATE WITH MECHANICAL PLANS FOR ALL MECHANICAL, POWER, AND DATA REQUIREMENTS.
12. COORDINATE WITH MECHANICAL DRAWINGS FOR ALL PLUMBING AND MECHANICAL PENETRATIONS.

	SLAB PENETRATION
	SLAB STEP SYMBOL
	SLAB SLOPE SYMBOL
	CONCRETE SLAB - STRUCTURAL
	AREA OF RECESSED SLAB - STRUCTURAL / ARCHITECTURAL
	AREA OF OVERBUILT SLAB - ARCHITECTURAL



9300 MARSAC AVE
PARK CITY, UT 84060



isions:

A2.1A.02

