


1. WHERE WALLS ALIGN TO GRID, LOCATE FACE OF STUD OR FACE OF CONCRETE (GRID, U.N.O.)
2. FINISH FLOOR ELEVATION TYPICAL, ACROSS LEVEL U.N.O.
3. REFER TO A.D. 10 AND A.D. 11 FOR CONCRETE
4. ALL DIMENSIONS ARE TO FACE OF CONCRETE AND CENTERLINE OF CONCRETE (GRID, U.N.O.)
5. TO CUBES 4' A.F. MAXIMUM 4' A.F., WHERE SLAB IS SLOPED, U.N.O.
6. MIN. 1% SLOPE TO DRAIN
7. TOP OF CONCRETE SLAB ELEVATIONS PROVIDED FOR REFERENCE, CONTRACTOR SHALL CONSIDER FINISH FLOOR ELEVATIONS PROVIDED ON ARCHITECTURAL PLANS AND ADJUST CONCRETE TO NECESSARY ELEVATION
8. CEILING HEIGHTS MEASURED FROM TOP OF CONCRETE - SEE SECTIONS
9. COORDINATE WITH ALL OTHER TRADES FOR ELEVATIONS, DETAILS AND CONDITIONS
10. COORDINATE WITH STRUCTURAL FRAMING PLANS AND SHEAR WALL PLANS FOR SIZE, DETAILS, AND REINFORCING FOR COLUMNS, BEAMS, SHEAR WALLS, ETC.
11. COORDINATE WITH ELECTRICAL, MECHANICAL, POWER, AND DATA REQUIREMENTS
12. COORDINATE WITH MECHANICAL DRAWINGS FOR ALL PLUMBING AND MECHANICAL PENETRATIONS

	SLAB PENETRATION
	SLAB STEP SYMBOL
	SLAB SLOPE SYMBOL
	CONCRETE SLAB - STRUCTURAL
	AREA OF RECESSED SLAB - STRUCTURAL / ARCHITECTURAL
	AREA OF OVERBUILT SLAB - ARCHITECTURAL



9300 MARSAC AVE
PARK CITY, UT 84060



principal architect TK, KM
project manager TM, JB, SL, MD
drawn by SK, SS, JR, CP, EA,
JF, BD
checked by JB
job no. 20052
date 05/17/2024

[illegible]

FC SET 2 OF 3
05/17/2024

A2.1C.01

