


1. DIMENSIONS ARE TO FACE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS, UNO
2. DIMENSIONS ARE TO CENTERLINE OF DEMISING WALLS, UNO
3. ALL EXPOSED STRUCTURAL STEEL TO RECEIVE 1 HR INTUMESCENT PAINTING, UNO
4. EXTERIOR WALLS, FRAMES TO BE SET BACK SIX" FROM FACE OF CONCRETE TO ALLOW FOR FLUSH ALIGNMENT OF SHEATHING TO EDGE OF SLAB, UNO
5. CASEWORK DIMENSIONS ARE TO FACE OF FINISH UNO.
6. SEE SHEETS A0 10 AND A0 11 FOR ASSEMBLIES.
7. ALL CORRIDOR WALLS ARE TYPE E6, UNO
8. ALL DEMISING WALLS ARE TYPE J6, UNO
9. ALL INTERIOR PARTITIONS ARE TYPE A8, UNO
10. ALL FURRING ABOVE CONCRETE STRUCTURAL COLUMNS TYPE G1, UNO
11. ALL VENT SHAFT WALLS ARE TYPE K4, UNO
12. REFER TO LIFE SAFETY PLANS A0 30 - A0 34 FOR FULL EXPLANATION OF FIRE RATED WALLS, UNO
13. UNIT PLAN FLOORS ON SHEETS A0 42 - A0 48
14. ALL OWNER PARKING STALLS SHALL INCLUDE EV INFRASTRUCTURE.
15. REFER TO SHEET A0 08 FOR ANSI TYPE B ACCESSIBILITY REQUIREMENTS
16. REFER TO SHEET A0 09 FOR ANSI TYPE A ACCESSIBILITY REQUIREMENTS
17. REFER TO SHEET A0 09 FOR ADA PUBLIC ACCESSIBILITY REQUIREMENTS
18. ALL MECHANICAL EQUIPMENT LOCATED WITHIN ELEVATOR/MECHANICAL EQUIPMENT ENCLOSURE



9300 MARSAC AVE
PARK CITY, UT 84060



o. date _____ by _____

A2.3B.23

