

RCP GENERAL NOTES

1. SPOT ELEVATIONS ARE RELATIVE TO FINISH FLOOR LEVEL AND INDICATE BOTTOM OF FINISH 2. ALL CEILINGS 9'-0" AFF U.N.O. 3. ALL CEILINGS ASSEMBLY C11 U.N.O.

4. ALL DIMENSIONS TO FACE OF FINISH U.N.O. 5. SEE CONCRETE PLANS FOR EXTENT OF CONCRETE SLABS AND BEAMS

- 6. OCCUPIABLE SPACES, HABITABLE SPACES AND CORRIDORS SHALL HAVE A CEILING HEIGHT OF NOT LESS THAN 7 FEET AND 6 INCHES. BATHROOMS, TOILET ROOMS, KITCHENS, STORAGE ROOMS AND LAUNDRY ROOMS SHALL HAVE A CEILING HEIGHT OF NOT LESS THAN 7 FEET. 7. SEE SHEET A0.10 AND A0.11 FOR FLOOR/CEILING ASSEMBLIES. 8. SEE ELECTRICAL AND LIGHTING DRAWINGS FOR LIGHTING LAYOUTS AND ADDITIONAL INFORMATION NOT SHOWN ON ARCHITECTURAL RCP DRAWINGS.
- 9. REFER TO MECHANICAL FOR SPRINKLER AND EXTINGUISHER TYPE AND FOR LOCATIONS. 10. ALL WALL-MOUNTED FIXTURES IN COMMON AREAS AND AMENITY LEVELS TO PROJECT 4" MAXIMUM FROM WALL FACE OR BE 6'-8" MINIMUM TO THE UNDERSIDE OF THE FIXTURE AFF. 11. SMOKE DETECTORS SHALL BE LOCATED A MINIMUM OF 3'-0" FROM SUPPLY AIR DIFFUSERS. 12. CENTER SPRINKLER HEAD LOCATIONS BETWEEN LIGHTING FIXTURES AND/OR SMOKE DETECTORS, TYPICAL. LOCATION AND SPACING TO BE DETERMINED WITH APPROVED SHOP DRAWINGS. PROVIDE SIDE ARMS WHERE HEADS AND OTHER CEILING FIXTURES MAY BE IN CONFLICT. ALIGN ALL HEADS AND FIXTURES ORTHAGONALLY.
- 13. FIRE-RATED CEILINGS SHALL ALWAYS BE CONTINUOUS ABOVE DROPPED CEILINGS OR SOFFITS WITH FASTENING AND JOINT TAPE AS REQUIRED FOR SPECIFIED RATING. 14. FIRE-RATED CEILINGS SHALL ALWAYS BE CONTINUOUS OVER CHASES/FURRED-OUT SPACES TO PREVENT THE WALL CAVITY FROM COMMUNICATING WITH THE FLOOR/CEILING CAVITY. FIRESTOP ALL PENETRATIONS OF FIRE-RATED FLOOR/CEILING ASSEMBLIES. 15. SEE MECHANICAL DRAWINGS FOR DUCT ROUTING. SEE MECHANICAL DRAWINGS FOR
- ADDITIONAL INSULATION REQUIREMENTS AT DUCTS. 16. CEILING ACCESS PANELS ARE REQUIRED AT ALL DAMPERS, VALVES, TELECOM ACCESS POINTS, AND SOME MECHANICAL EQUIPMENT. COORDINATE LOCATIONS PRIOR TO INSTALLATION OF ANY OF THESE SYSTEMS

ELECTRICAL AND MECHANICAL INFORMATION ARE SHOWN FOR COORDINATION PURPOSES. REFER TO MECHANICAL DRAWINGS AND ELECTRICAL DRAWINGS FOR GENERAL INFORMATION AND LOCATIONS.

HATCH PATTERN INDICATE EXTENT OF CEILING TYPES REFER TO CEILING ASSEMBLY FOR DETAIL INFORMATION

WOOD CEILING

STONE TILE

SUSPENDED GYPSUM WALL BOARD

WAP

S

 \square

STONE TILE
ACOUSTICAL CEILING TILE
PINNED INSULATION
FABRIC PANEL PER GOLF SIMULATOR
COMPOSITE METAL WALL PANEL
SQUARE RECESSED DOWNLIGHT
DECORATIVE SCONCE
DECORATIVE CUSTOM CHANDELIER
ROUND PENDANT LIGHT
J-BOX
LENSED LINEAR UTILITY STRIP
CONCEALED LINEAR UNDERCABINET STRIP
TRACK / RAIL / LINEAR LED
SURFACE-MOUNTED LIGHT BAR SURFACE MOUNT PANEL
SPRINKLER
SMOKE DETECTOR
COMBINATION SMOKE / CARBON MONOXIDE DETECTOR
FIRE ALARM SPEAKER
FIRE ALARM STROBE
FIRE ALARM COMBINATION SPEAKER / STROBE
EXIT SIGN
SECURITY CAMERA
WIRELESS ACCESS POINT
AV SPEAKER
MOTORIZED SINGLE ROLLER SHDAE - EQ-02.00
MOTORIZED DOUBLE ROLLER SHDAE - EQ-02.01
CEILING FAN - MECH EXHAUST
MECHANICAL LINEAR GRILLE
CEILING ACCESS PANEL
CEILING CONTROL POINT



RCP - TOWER C - LVL P1 A6.1C.01