



	LH	LIGHT HAZARD: SYSTEM PROVIDING A DENSITY OF .10 GPMSQFT. OVER DESIGN AREA OF 1,500 SQ. FT. WITH 100 GPM HOSE ALLOWANCE
	RES	RESIDENTIAL HAZARD: SYSTEM PROVIDING A DENSITY OF .10 GPMSQFT. OVER DESIGN AREA OF 4 SPRINKLERS. WITH 100 GPM HOSE ALLOWANCE
	OH1	ORDINARY HAZARD GROUP 1: SYSTEM PROVIDING A DENSITY OF .15 GPMSQFT. OVER DESIGN AREA OF 1,500 SQ. FT. WITH 250 GPM HOSE ALLOWANCE
	OH2	ORDINARY HAZARD GROUP 2: SYSTEM PROVIDING A DENSITY OF .20 GPMSQFT. OVER DESIGN AREA OF 1,500 SQ. FT. WITH 250 GPM HOSE ALLOWANCE
	EX1	EXTRA HAZARD GROUP 1: SYSTEM PROVIDING A DENSITY OF .30 GPMSQFT. OVER DESIGN AREA OF THE ENTIRE ROOM WITH 500 GPM HOSE ALLOWANCE
	NS	NON-SPRINKLERED AREA

FP1.02