




	LH	LIGHT HAZARD: SYSTEM PROVIDING A DENSITY OF .10 GRMS/SQ. OVER DESIGN AREA OF 1,500 SQ. FT. WITH 100 GPM/HQZE ALLOWANCE
	RES	RESIDENTIAL HAZARD: SYSTEM PROVIDING A DENSITY OF .10 GRMS/SQ. OVER DESIGN AREA OF 4 SPRINKLERS, WITH 100 GPM/HQZE ALLOWANCE
	QH1	ORDINARY HAZARD GROUP 1: SYSTEM PROVIDING A DENSITY OF .15 GRMS/SQ. OVER DESIGN AREA OF 1,500 SQ. FT. WITH 250 GPM/HQZE ALLOWANCE
	QH2	ORDINARY HAZARD GROUP 2: SYSTEM PROVIDING A DENSITY OF .20 GRMS/SQ. OVER DESIGN AREA OF 1,500 SQ. FT. WITH 250 GPM/HQZE ALLOWANCE
	EX1	EXTRA HAZARD GROUP 1: SYSTEM PROVIDING A DENSITY OF .30 GRMS/SQ. OVER DESIGN AREA OF THE ENTIRE ROOM WITH 500 GPM/HQZE ALLOWANCE
	NS	NON-SPRINKLERED AREA

FP1.04