





FIRE PROTECTION DESIGN HATCH LEGEND

	LH	LIGHT HAZARD, SYSTEM PROVIDING A DENSITY OF .10 GPM/SQ OVER DESIGN AREA OF 1,500 SQ FT WITH 100 GPM HOSE ALLOWANCE
	RES	RESIDENTIAL HAZARD, SYSTEM PROVIDING A DENSITY OF .10 GPM/SQ OVER DESIGN AREA OF A SPRINKLERS, WITH 100 GPM HOSE ALLOWANCE
	OHT	ORDINARY HAZARD GROUP 1, SYSTEM PROVIDING A DENSITY OF .15 GPM/SQ OVER DESIGN AREA OF 1,500 SQ FT, WITH 250 GPM HOSE ALLOWANCE
	OHT	ORDINARY HAZARD GROUP 2, SYSTEM PROVIDING A DENSITY OF .20 GPM/SQ OVER DESIGN AREA OF 1,500 SQ FT, WITH 250 GPM HOSE ALLOWANCE
	EXT	EXTRA HAZARD GROUP 1, SYSTEM PROVIDING A DENSITY OF .30 GPM/SQ OVER DESIGN AREA OF THE ENTIRE ROOM WITH 500 GPM HOSE ALLOWANCE
	NS	NON-SPRINKLERED AREA