



S0 XX	DRAWING INDEX, ABBREVIATIONS, LEGENDS, GENERAL NOTES
S1 XX	LOAD DIAGRAMS
S2 XX	PLANS
S3 XX	ELEVATIONS
S4 XX	TYPICAL DETAILS AND SCHEDULES
S5 XX	CONCRETE SECTIONS AND DETAILS
S6 XX	STEEL SECTIONS AND DETAILS

1. REFERENCE ELEVATION IS 8314' - 1". TOP OF MAT IS AT THE REFERENCE ELEVATION UNLESS NOTED OTHERWISE. SEE ARCHITECTURAL PLANS FOR DIMENSIONS OF ALL SLAB EDGES, OPENINGS, SLOPES, AND DEPRESSIONS NOT DEFINED ON THE STRUCTURAL PLANS.
2. MAT FOUNDATION IS 3'-0" THICK UNLESS NOTED OTHERWISE. UPON REACHING THE MAT FOUNDATION SUBGRADE ELEVATION, SOIL CONDITIONS SHALL BE EVALUATED AND APPROVED BY THE GEOTECHNICAL ENGINEER OF RECORD.
3. SHEAR WALL OPENINGS, WALL ENDS, AND WALL LOCATIONS ARE DIMENSIONED RELATIVE TO GRID LINES ON THE SHEAR WALL ELEVATION.
4. BASEMENT WALLS SHALL BE RESTRAINED AT EACH FLOOR BY THE STRUCTURAL SLAB AND AT THE BOTTOM OF THE MAT, AND SHALL HAVE REACHED DESIGN STRENGTH PRIOR TO PLACING BACKFILL AND/OR DE-TENSIONING TIE-BACK ANCHORS.
5. BASEMENT WALLS ARE DESIGNED FOR A FULLY DRAINED CONDITION IN THE RETAINED SOIL.
6. BASEMENT WALL REINFORCEMENT IS SHOWN ON THE BASEMENT WALL ELEVATIONS.
7. THE STRUCTURAL SLAB IS A 10-INCH THICK MILD TWO-WAY SLAB UNLESS NOTED OTHERWISE. SEE THE TYPICAL MILD SLAB DETAILS.

- 

Reserved for permit stamp

159 South Jackson St, Suite 600  
Seattle, Washington 98104 USA  
+1 208 824 5670 [olsorkundig.com](mailto:olsorkundig.com)

Olson Kundig

**SOMMET BLANC - ABC**  
DEER VALLEY, UTAH

**MAGNUSSON  
KLEMENCIC**  
ASSOCIATES

Structural + Civil Engineers

Seattle Chicago  
www.mka.com  
206 292 1200

principal architect \_\_\_\_\_  
project manager \_\_\_\_\_  
drawn by \_\_\_\_\_  
checked by \_\_\_\_\_  
job no. 20052  
date 05/17/2024

revisions:

04/08/2024	IFC SET 1 OF 3
11/18/2022	95% CD

no.	date	by
-----	------	----

IFC SET 2 OF 3

05/17/2024

TOWER A LEVEL B1  
FRAMING PLAN

S2.A.01