




S0 XX	DRAWING INDEX, ABBREVIATIONS, LEGENDS, GENERAL NOTES
S1 XX	LOAD DIAGRAMS
S2 XX	PLANS
S3 XX	ELEVATIONS
S4 XX	TYPICAL DETAILS AND SCHEDULES
S5 XX	CONCRETE SECTIONS AND DETAILS
S6 XX	STEEL SECTIONS AND DETAILS

1. REFERENCE FLOOR ELEVATION IS 8436' - 6". TOP OF STRUCTURAL CONCRETE SLAB IS 8436' - 5" UNLESS NOTED OTHERWISE. SEE ARCHITECTURAL DRAWINGS FOR DRAINAGE SLOPES NOT SHOWN.
2. STRUCTURAL SLAB IS A 12-INCH THICK UNBONDED POST-TENSIONED TWO-WAY SLAB UNLESS NOTED OTHERWISE. SEE TYPICAL POST-TENSIONED SLAB DETAILS FOR ADDITIONAL INFORMATION.
3. THE MINIMUM NUMBER OF REQUIRED POST-TENSIONING TENDONS IS SHOWN ON THE DRAWINGS. FINAL COUNT, LAYOUT, AND LIVE END LOCATION IS PER DEFERRED DESIGN-BUILD SUBMITTAL PROVIDED BY THE CONTRACTOR.
4. CONCRETE PLACED IN THE SLAB/SHEAR WALL INTERSECTION, INCLUDING COUPLING BARS, SHALL HAVE MINIMUM CONCRETE STRENGTH EQUAL TO THAT SPECIFIED FOR THE SHEAR WALLS.
5. CONCRETE PLACED IN THE SLAB/COLUMN INTERSECTION SHALL HAVE MINIMUM CONCRETE STRENGTH AS SHOWN IN THE GENERAL NOTES, BUT NO LESS THAN THAT SPECIFIED FOR THE COLUMNS DIVIDED BY 1.4.
6. COORDINATE LOCATION OF ALL EMBEDS WITH MECHANICAL, ELECTRICAL, PLUMBING, AND EXTERIOR WALL SYSTEMS PRIOR TO CASTING THE SLAB.

- 



Reserved for permit stamp

159 South Jackson St, Suite 600  
Seattle, Washington 98104 USA  
+1 206 624 5870 [olsonskundig.com](mailto:olsonskundig.com)

Olson Kundig

project: **SOMMET BLANC - ABC**  
**DEER VALLEY, UTAH**

MAGNUSSON  
KLEMENCIC  
ASSOCIATES

**Structural + Civil Engineers**  
Seattle Chicago  
www.mika.com  
206.292.1200

principal architect \_\_\_\_\_  
project manager \_\_\_\_\_

checked by \_\_\_\_\_  
job no. 20052  
date 05/17/2024

revisions

04/08/2024 IFC SET 1 OF 3

no.	date	by
-----	------	----

IFC SET 2 OF 3

05/17/2024

TOWER B LEVEL 7  
FRAMING PLAN

**S2.B.17**