

1. DIMENSIONS ARE TO FACE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS. UNO
2. DIMENSIONS ARE TO CENTERLINE OF DEMISING WALLS. UNO
3. ALL EXPOSED STRUCTURAL STEEL TO RECEIVE 1R INTRINSIC EMULSION PAINTING. UNO
4. AT EXPOSED EXTERIOR WALLS, FINISH TO BE SET BACK 50" FROM FACE OF CONCRETE TO ALLOW FOR FLUSH ALIGNMENT OF SHEATHING TO FACE OF STUD. UNO
5. CASEWORK DIMENSIONS AND TO FACE OF FINISH. UNO
6. SEE SHEETS 01 10 AND 01 11 FOR ASSEMBLIES.
7. ALL CORRIDOR WALLS ARE TYPE **E6**. UNO
8. ALL DEMISING WALLS ARE TYPE **J6**. UNO
9. ALL INTERIOR PARTITIONS ARE TYPE **A6**. UNO
10. ALL FURRING AROUND CONCRETE PARTITIONS AND STRUCTURAL COLUMNS TYPE **G1**. UNO
11. ALL VENT SHAF T WALLS ARE TYPE **K4**. UNO
12. REFER TO LIFE SAFETY PLANS 03 30 - 03 34 FOR FULL EXTENT OF FIRE RATED WALLS.
13. UNIT LAYOUT PLANS ON SHEETS S2 44 - A2 48
14. ALL OWNER PARKING STALLS SHALL INCLUDE INFRASTRUCTURE.
15. REFER TO SHEET 08 08 FOR ANSI TYPE B ACCESSIBILITY REQUIREMENTS.
16. REFER TO SHEET 07 07 FOR ANSI TYPE A ACCESSIBILITY REQUIREMENTS.
17. REFER TO SHEET 08 08 FOR ADA COMPLIANCE ACCESSIBILITY REQUIREMENTS.
18. ALL MECHANICAL EQUIPMENT LOCATED WITHIN ELEVATOR/MECHANICAL EQUIPMENT ENCLOSURE.

