Location: 9300 Marsac Avenue (B2 East Parcel), Park City, Utah

IFC Issuance: 07/19/2024 Project Number: 20052

Product Info

Manufacturer: TOTO Plumbing Products

Style/Series: Aimes Washlet + S500e One-Piece Toilet

Sales Rep

Primary Jodi Nelson Email: jodi@mld.com Office Phone: (801)466-0990

Attributes

Location: Units - Bath

Product: MW6263046CEFG(A)

Dimension: 17-5/16"W x 29-3/16"D x 23-5/16"H w/ Lid

up x 17-5/8"SH Finish: 01 Cotton **GPF:** 1.28 GPF



PL-03.01

Seattle, Washington

Olson Kundig

Provide Manufacturer's warranty information
 Provide manufacturer's assembly instructions including a list pf parts included in all shipments.
 Olson Kundig owns all copyrights to the design of custom products. Photography of product is prohibited without the expressed written consent by Olson Kundig.
 All drawings provided are for reference only, and not for construction

TOTO_®

MW6263046CEFG(A)

Aimes® WASHLET®+ S500e One-Piece Toilet - 1.28 GPF

FEATURES

- Concealed supply connection for seamless installation
- TORNADO FLUSH® system, high-efficiency (1.28 GPF/4.8 LPF)
- CEFIONTECT® ceramic glaze prevents debris and mold from sticking to ceramic surfaces
- Completely skirted design for a sleek and understated look that's easier to clean
- Universal Height
- 12" Rough-in
- Chrome plated trip lever
- Elongated front bowl and WASHLET+ S500e and tank set
- EWATER+® auto-cleans wand and bowl
- On-demand remote function cleans wand with EWATER+
- PREMIST of bowl before each use
- Remote control operated
- Auto Flush available as upgrade

MODELS & COMPONENTS

MW6263046CEFGA (#01)

With CEFIONTECT ceramic glaze, WASHLET+ S500e with contemporary design and Auto Flush

- CST626CEFGAT40
 Elongated toilet with CEFIONTECT
- SW3046AT40 WASHLET+ S500e - Auto Flush compatible
- THU767 Auto Flush Kit
- MW6263046CEFG (#01)

Same as MW6263046CEFG without Auto Flush

- CST626CEFGT40 Elongated toilet with CEFIONTECT
- SW3046T40 WASHLET+ S500e - Non Auto Flush compatible

Optional Components

- TSU03W.10R 10" Unifit Rough-In
- TSU03W.14R 14" Unifit Rough-In
- THU311N#PN
 Trip Lever Polished Nickel
- THU311N#BN
 Trip Lever Brushed Nickel

COLORS/FINISHES

#01 Cotton



TORNADO FLUSH

€ EWATER+

CEFIONTECT



Universal Height

PRODUCT SPECIFICATION

The one-piece high-efficiency TORNADO FLUSH system toilet shall be 1.28 GPF/4.8 LPF. Toilet shall be 12" Unifit rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl with Polished Chrome trip lever. Toilet shall be TOTO Model MW6263046CEFG_#01

See SW3056(A)T40 Specification Sheet for details on included WASHLET.

CODES/STANDARDS

- Meets or exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA Watersense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements







Aimes® WASHLET®+ S500e One-Piece Toilet - 1.28 GPF

SPECIFICATIONS


Water Use	1.28 GPF (4.8 LPF)			
Flush System	TORNADO FLUSH®			
Min. Water Pressure	8 psi (Flowing)			
Water Surface	7-3/4" x 9-3/8"			
Trap Diameter	2-1/8"			
Rough-in	12" (10" & 14" Optional)			
Trap Seal	2-1/8"			
Warranty	One Year Limited Warranty			
Material	Vitreous China			
Shipping Weight	119 lbs			
Shipping Dimensions	32"L x 20"W x 17-3/4" H ¹ x 28-3/4" H ²			

See SW3056(A)T40 Specification Sheet for details on included WASHLET.

INSTALLATION NOTES


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS





These dimensions and specifications are subject to change without notice