


1. WHERE WALLS ALIGN TO GRID, LOCATE FACE OF STUO OR FACE OF CONCRETE AT GRID, U.N.O.
2. FINISH FLOOR ELEVATION THRUOUT, ACROSS LEVEL, U.N.O.
3. REFER TO A.D. 10 AND A.D. 11 FOR FINISH ASSEMBLIES
4. ALL DIMENSIONS ARE FACE OF CONCRETE AND CENTERLINE OF CONCRETE, U.N.O.
5. U.S. 2, CURBS 4" F.F., MAXIMUM 6" F.F., WHERE SLOPE IS SLOPED, U.N.O.
6. MIN. 1% SLOPE TO DRAIN
7. TOP OF CONCRETE SLAB ELEVATIONS PROVIDED FOR REFERENCE, CONTRACTOR SHALL COORDINATE WITH FINISH FLOOR ELEVATIONS PROVIDED ON ARCHITECTURAL PLANS AND ADJUST THEREFOR
8. CEILING HEIGHTS MEASURED FROM TOP OF CONCRETE - SEE SECTIONS
9. COORDINATE WITH ALL OTHER TRADES FOR FINISH MATERIALS AND DETAILS
10. COORDINATE WITH STRUCTURAL FRAMING PLANS AND SHEAR WALLS FOR PLANS, DETAILS, AND REINFORCING FOR COLUMNS, BEAMS, SHEAR WALLS, ETC.
11. COORDINATE WITH ELECTRICAL, MECHANICAL, PLUMBING, POWER, AND DATA REQUIREMENTS
12. COORDINATE WITH MECHANICAL DRAWINGS FOR ALL PLUMBING AND MECHANICAL PENETRATIONS

	SLAB PENETRATION
	SLAB STEP SYMBOL
	SLAB SLOPE SYMBOL
	CONCRETE SLAB - STRUCTURAL
	AREA OF RECESSED SLAB - STRUCTURAL / ARCHITECTURAL
	AREA OF OVERBUILT SLAB - ARCHITECTURAL



SUMMIT BLANC
9300 MARSAC AVE
PARK CITY, UT 84060

