



1. WHERE WALLS ALONG TO GRID, LOCATE FACE OF STUO OR FACE OF CONCRETE AT GRID, U.N.O.
2. FINISH FLOOR ELEVATION THRUOUT, ACROSS LEVEL, U.N.O.
3. REFER TO A/D 10 AND 11 FOR ALL ASSEMBLIES
4. ALL DIMENSIONS ARE FACE OF CONCRETE AND CENTERLINE OF CONCRETE, U.N.O.
5. U.S. CURBS 4" F.F., MAXIMUM 6" F.F., WHERE SLOPE IS SLOPED, U.N.O.
6. MIN. 1% SLOPE TO DRAIN
7. TOP OF CONCRETE SLAB ELEVATIONS PROVIDED FOR REFERENCE, CONTRACTOR SHALL COORDINATE WITH FINISH FLOOR ELEVATIONS PROVIDED ON ARCHITECTURAL PLANS AND ADJUST THEREFOR
8. CEILING HEIGHTS MEASURED FROM TOP OF CONCRETE - SEE PLANS.
9. COORDINATE WITH ALL ELECTRICAL, MECHANICAL, PLUMBING, AND HVAC DETAILS
10. COORDINATE WITH STRUCTURAL FRAMING PLANS AND SHEAR WALL - SEE DETAILS.
11. AND REINFORCING FOR COLUMNS, BEAMS, SHEAR WALLS, ETC.
12. COORDINATE WITH ELECTRICAL, MECHANICAL, PLUMBING, POWER, AND DATA REQUIREMENTS
13. COORDINATE WITH MECHANICAL DRAWINGS FOR ALL PLUMBING AND MECHANICAL PENETRATIONS

	SLAB PENETRATION
	SLAB STEP SYMBOL
	SLAB SLOPE SYMBOL
	CONCRETE SLAB - STRUCTURAL
	AREA OF RECESSED SLAB - STRUCTURAL / ARCHITECTURAL
	AREA OF OVERBUILT SLAB - ARCHITECTURAL



SUMMIT BLANC
9300 MARSAC AVE
PARK CITY, UT 84060



MEP Engineer
WSP USA
1001 Fourth Ave., Suite 3100
Seattle, WA 98154

05/31/2024

A2.1A.02

