

1. DIMENSIONS ARE TO FACE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS, UNO
2. DIMENSIONS ARE TO CENTERLINE OF DEMISING WALLS, UNO
3. ALL CONCRETE STRUCTURAL STALLS SHALL BE 18" MIN. THICK CONCRECENT PANEL UNO
4. AT FRAMED EXTERIOR WALLS, FRAMING TO BE SET BACK 8" FROM FACE OF CONCRETE TO ALLOW FOR FLUSH ALIGNMENT OF SHEATHING TO EDGE OF SLAB, UNO
5. CASEWORK DIMENSIONS ARE TO FACE OF FINISH, UNO
6. SEE SHEETS AO 10 AND AO 11 FOR ASSEMBLIES
7. ALL CORRIDOR WALLS ARE TYPE EB, UNO
8. ALL DEMISING WALLS ARE TYPE JB, UNO
9. ALL INTERIOR PARTITIONS ARE TYPE AB, UNO
10. ALL FURRING AROUND CONCRETE STRUCTURAL COLUMNS TYPE G1, UNO
11. ALL VENT SHAFT WALLS ARE TYPE K4, UNO
12. REFER TO LIFE SAFETY PANELS AO 30- AO 34 FOR FULL EXHIBIT OF FIRE RATED WALLS.
13. UNO PLANT LAYOUTS ON SHEETS A24-A 29
14. ALL OWNER PARKING STALLS SHALL INCLUDE EV INFRASTRUCTURE.
15. REFER TO SHEET AO FOR ANSI TYPE B ACCESSIBILITY REQUIREMENTS.
16. REFER TO SHEET AO FOR ADA TYPE B ACCESSIBILITY REQUIREMENTS.
17. REFER TO SHEET AO FOR ADA PLACED SPACE ACCESSIBILITY REQUIREMENTS.
18. ALL MECHANICAL EQUIPMENT LOCATED WITHIN ELEVATOR/MECHANICAL EQUIPMENT ENCLOSURE.

