

1. WHERE WALLS ALIGN TO GRID, LOCATE FACE OF STUD OR FACE OF CONCRETE AT GRID, U.N.O.
2. FINISH FLOOR ELEVATION TOPIAL ACROSS LEVEL.
3. REFER TO 10 TO 40 AND 10 FOR ASSEMBLIES.
4. FINISH DIMENSIONS ARE TO FACE UNLESS OTHERWISE NOTED AND CENTERLINE OF CONCRETE, U.N.O.
5. 10, 20, CUBES 4" X 4" MAXIMUM IF 4" X 4", WHERE SLOPE IS SLOPED, U.N.O.
6. 10% IS SLOPE TO DRAIN.
7. TOP OF CONCRETE SLAB ELEVATIONS PROVIDED FOR REFERENCE. CONTRACTOR SHALL COORDINATE WITH FINISH FLOOR ELEVATIONS PROVIDED ON ARCHITECTURAL PLANS AND ADJUST AS NECESSARY.
8. CEILING HEIGHTS MEASURED FROM TOP OF CONCRETE - SEE SECTIONS.
9. COORDINATE WITH ALL OTHERS FOR FINISH FLOOR, CEILING, POWER, AND GAS DETAILS.
10. COORDINATE WITH STRUCTURAL, FRAMING PLANS AND SHEAR WALL PLANS, DETAILS, AND REINFORCING FOR COLUMNS, BEAMS, SHEAR WALLS, ETC.
11. COORDINATE WITH ELECTRICAL, MECHANICAL, POWER, AND DATA REQUIREMENTS.
12. COORDINATE WITH MECHANICAL DRAWINGS FOR ALL PLUMBING AND MECHANICAL PENETRATIONS.

	SLAB PENETRATION
	SLAB STEP SYMBOL
	SLAB SLOPE SYMBOL
	CONCRETE SLAB - STRUCTURAL
	AREA OF RECESSED SLAB - STRUCTURAL / ARCHITECTURAL
	AREA OF OVERSLUMP SLAB - ARCHITECTURAL



SCALE: 1/8" = 1'-0"

