


2. DIMENSIONS ARE TO FACE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS, UNO
3. DIMENSIONS ARE TO CENTERLINE OF EXTERIOR WALLS. UNO
4. ALL EXPOSED STRUCTURAL STEEL TO RECEIVE H/R INJUNCTEMENT PAINTING, UNO
5. ALL FRAMED EXTERIOR WALLS TO RECEIVE 50 MM THICK 1:2:4 CONCRETE SLAB FROM FACE OF CONCRETE TO ALLOW FOR FLUSH ALIGNMENT OF SHEATHING TO EDGE OF SLAB. UNO
6. CASEWORK DIMENSIONS TO AND TO FACE OF FINISH. UNO
7. SEE SHEETS A0 10 AND A0 11 FOR ASSEMBLIES.
8. ALL CORRIDOR WALLS ARE TYPE IE6. UNO
9. ALL DEMISING WALLS ARE TYPE IE6. UNO
10. ALL INTERIOR PARTITIONS ARE TYPE A6. UNO
11. ALL FURRING AROUND CONCRETE STAIR AND CORRIDOR COLUMNS TYPE G1. UNO
12. ALL VENT SHAFT WALLS ARE TYPE K4. UNO
13. REFER TO LIFE SAFETY PLANS A0 30 - A0 34 FOR FULL EXTENT OF FIRE RATED WALLS.
14. UNO PLAN LAYOUTS ON SHEETS A2 44 - A2 48
15. ALL OWNER PARKING STALLS TO RECEIVE 100% FULLY ENCLOSED INFRASTRUCTURE.
16. REFER TO SHEET A0 08 FOR ANS TYPE 2 ACCESSIBILITY REQUIREMENTS.
17. REFER TO SHEET A0 07 FOR ANS TYPE 4 ACCESSIBILITY REQUIREMENTS.
18. REFER TO SHEET A0 06 FOR ANS TYPE 3 ACCESSIBILITY REQUIREMENTS.
19. ALL MECHANICAL EQUIPMENT LOCATED WITHIN ELEVATOR MECHANICAL ENCLOSURE.

SOMMET BLANC  
9300 MARSAC AVE  
PARK CITY, UT 84060



**MEP Engineer**  
**WSP USA**  
1001 Fourth Ave., Suite 3100  
Seattle, WA 98154

1	01/06/25	ASI 006
no.	date	

PLAN - TOWER B - LVL  
P1- AREA D

A2.3B.03d