

1. DIMENSIONS ARE TO FACE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS. UNO
2. DIMENSIONS ARE TO CENTERLINE OF DEMISING WALLS. UNO
3. ALL EXPOSED STRUCTURAL STEEL, TO RECEIVE 1 HR INTUMESCENT PAINTING. UNO
4. ALL EXTERIOR WALLS, FRAMES TO BE SET BACK 500 FROM FACE OF CONCRETE TO ALLOW FOR FLUSH ALIGNMENT OF SHEATHING TO EDGE OF SLAB. UNO
5. CASEWORK DIMENSIONS ARE TO FACE OF FINISH. UNO
6. SEE SHEETS A0 10 AND A0 11 FOR ACCESSORIES. UNO
7. ALL CORRIDOR WALLS ARE TYPE E6. UNO
8. ALL DEMISING WALLS ARE TYPE J6. UNO
9. ALL INTERIOR PARTITIONS ARE TYPE A6. UNO
10. ALL FURRING ABOVE CONCRETE SLAB ARE TYPE B6. UNO
11. ALL STRUCTURAL COLUMNS TYPE G1. UNO
12. ALL VENT SHAFT WALLS ARE TYPE K4. UNO
12. REFER TO LIFE SAFETY PLANS A0 30 - A0 34 FOR FULL EXTENT OF FIRE RATED WALLS. UNO
13. UNIT PLAN LAYOUTS ON SHEETS A0 44 - A0 48
14. ALL OWNER PARKING STALLS SHALL INCLUDE EV INFRASTRUCTURE. UNO
15. REFER TO SHEET A0 69 FOR ANSI TYPE B ACCESSIBILITY REQUIREMENTS. UNO
16. REFER TO SHEET A0 70 FOR ANSI TYPE A ACCESSIBILITY REQUIREMENTS. UNO
17. REFER TO SHEET A0 69 FOR AYS TYPE A SPACE ACCESSIBILITY REQUIREMENTS. UNO
18. ALL MECHANICAL EQUIPMENT LOCATED WITHIN ELEVATOR/MECHANICAL EQUIPMENT ENCLOSURE. UNO

Olson Kundig

9300 MARSAC AVE
PARK CITY, UT 84060



P USA
1 Fourth Ave., Suite 3100
Seattle, WA 98154

no.	date	by

A2.3A.02b

