




|       |                                                      |
|-------|------------------------------------------------------|
| S0.XX | DRAWING INDEX, ABBREVIATIONS, LEGENDS, GENERAL NOTES |
| S1.XX | LOAD DIAGRAMS                                        |
| S2.XX | PLANS                                                |
| S3.XX | ELEVATIONS                                           |
| S4.XX | TYPICAL DETAILS AND SCHEDULES                        |
| S5.XX | CONCRETE SECTIONS AND DETAILS                        |
| S6.XX | STEEL SECTIONS AND DETAILS                           |

1. REFERENCE FLOOR ELEVATION IS 8414'-6". TOP OF STRUCTURAL CONCRETE SLAB IS 8414'-5". UNLESS NOTED OTHERWISE. SEE ARCHITECTURAL DRAWINGS FOR DRAINAGE SLOPES NOT SHOWN.
2. STRUCTURAL SLAB IS AN 8-INCH THICK UNBONDED POST-TENSIONED TWO-WAY SLAB UNLESS NOTED OTHERWISE. SEE TYPICAL POST-TENSIONED SLAB DETAILS FOR ADDITIONAL INFORMATION.
3. THE MINIMUM NUMBER OF REQUIRED POST-TENSIONING TENDONS IS SHOWN ON THE DRAWINGS. FINAL COUNT, LAYOUT, AND LIVE END LOCATION IS PER DEFERRED DESIGN-BUILD SUBMITTAL PROVIDED BY THE CONTRACTOR.
4. CONCRETE PLACED IN THE SLAB/COLUMN INTERSECTION SHALL HAVE MINIMUM CONCRETE STRENGTH AS SHOWN IN THE GENERAL NOTES, BUT NO LESS THAN THAT SPECIFIED FOR THE COLUMN DIVIDED BY 1.4.
5. COORDINATE LOCATION OF ALL EMBEDS WITH MECHANICAL, ELECTRICAL, PLUMBING, AND EXTERIOR WALL SYSTEMS PRIOR TO CASTING THE SLAB.
6. SEE ARCHITECTURAL, MECHANICAL, PLUMBING, ELECTRICAL, AND OTHER DISCIPLINES DRAWINGS FOR OPENING SIZES AND LOCATIONS NOT SHOWN ON PLAN. SEE "TYPICAL OPENINGS AND EMBEDMENTS IN CONCRETE" DETAILS FOR OPENING PLACEMENT CRITERIA. NOTIFY THE STRUCTURAL ENGINEER OF ANY OPENINGS NOT SHOWN ON THE STRUCTURAL DRAWINGS FOR WHICH THE TYPICAL DETAILS DO NOT APPLY.

- 



Seattle Chicago  
www.mika.com  
206 292 1200

[illegible]

| no. | date | by |
|-----|------|----|
|-----|------|----|

05/17/2024

S2.C.14