


1. DIMENSIONS ARE TO FACE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS
2. DIMENSIONS ARE TO CENTERLINE OF DEMISING WALLS
3. EXPOSED STRUCTURAL STEEL RECEIVE TO BE 1/8" MINIMUM THICKNESS PAINTING, UNLESS OTHERWISE NOTED
4. CONCRETE WORK SHALL BE TO FACE OF FORMS
5. PROVIDE FOR PLUMB ALIGNMENT OF SHEATHING TO EDGE OF SLAB UNLESS OTHERWISE NOTED
6. CASEWORK DIMENSIONS SHALL BE TO FACE OF FINISH SURF
7. ALL CORRIDOR WALLS ARE TO FACE UNLESS NOTED
8. ALL CORRIDOR WALLS ARE TYPE EA UNLESS NOTED
9. ALL DEMISING WALLS ARE TYPE EA UNLESS NOTED
10. ALL INTERIOR PARTITIONS ARE TYPE A6 UNLESS NOTED
11. ALL FLOORING ABOVE CONCRETE STRUCTURAL COLUMNS TYPE Q1 UNLESS NOTED
12. ALL LIFT CHART WALLS ARE TYPE A6 UNLESS NOTED
13. REFER TO LIFE SAFETY PLANS 400-04-34 FOR FULL EXTENT OF FIRE RATED WALLS. UNLESS OTHERWISE NOTED
14. ALL OWNER PARKING STALLS SHALL INCLUDE VEHICLE INFRASTRUCTURE
15. REFER TO SHEET 400-08 FOR PARKING STALL REQUIREMENTS
16. REFER TO SHEET 400-09 FOR STALL TYPE ACCESSIBILITY REQUIREMENTS
17. REFER TO SHEET 400-10 FOR ADA PUBLIC SPACE ACCESSIBILITY REQUIREMENTS
18. ALL EQUIPMENT LOCATED WITHIN ELEVATOR SHAFTS, EQUIPMENT SHAFTS OR EQUIPMENT ROOMS SHALL BE TO FACE UNLESS OTHERWISE NOTED
19. REFER TO COORDINATE WITH PREPARE MANUFACTURE GUIDELINES FOR VENTING



SOMMET BLANC
9300 MARSAC AVE
PARK CITY, UT 84060



MEP Engineer
WSP USA
1001 Fourth Ave., Suite 3100
Seattle, WA 98154

Q	04/07/25	ASI 010
N	04/07/25	ASI 009
no.	date	by

PLAN - TOWER C - LVL 7

A2.2C.17

