

1. DIMENSIONS ARE TO EDGE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS, UNO.
2. DIMENSIONS ARE TO CENTERLINE OF DEMISING WALLS, UNO.
3. ALL EXPOSED STRUCTURAL STEEL TO RECEIVE 1R HT INTERMEDIATE PAINTING, UNO.
4. AT FRAMED EXTERIOR WALLS, FRAMING TO BE SAVED 8" FROM FACE OF CONCRETE TO ALLOW FOR FLUSH ALIGNMENT OF SHEATHING TO EDGE OF SLAB, UNO.
5. CASEWORK DIMENSIONS ARE TO FACE OF FINISH, UNO.
6. PEEPSH SHEET 10.0 AND 10.1 FOR ASSEMBLIES.
7. ALL CORRIDOR WALLS ARE TYPE E6, UNO.
8. ALL DEMISING WALLS ARE TYPE J6, UNO.
9. ALL INTERIOR PARTITIONS ARE TYPE A6, UNO.
10. ALL FURRING AROUND CONCRETE STRUCTURAL COLUMNS TYPE G1, UNO.
11. ALL VENT SHAFT WALLS ARE TYPE K4, UNO.
12. ALL VENT SHAFT SAFETY PLANS 0.30 - 0.34 FOR FULL EXISTENT OF FIRE RATED WALLS.
13. UNIT PLAN LAYOUTS ON SHEETS A2-30 - A2-48.
14. ALL OWNER PARKING STALLS SHALL INCLUDE VEV INFRASTRUCTURE.
15. REFER TO SHEET A0.08 FOR ANSI TYPE B ACCESSIBILITY REQUIREMENTS.
16. REFER TO SHEET A0.07 FOR ANSI TYPE A ACCESSIBILITY REQUIREMENTS.
17. REFER TO SHEET A0.08 FOR ADA PUBLIC SPACE ACCESSIBILITY REQUIREMENTS.
18. REFER TO SHEET A0.08 FOR ADA ELEVATOR MECHANICAL EQUIPMENT ENCLOSURE.
19. CONTRACTOR TO COORDINATE WITH ERECTOR MANUFACTURER GUIDELINES FOR VENTING.

