

PLAN GENERAL NOTES

1. DIMENSIONS ARE TO FACE OF STUD OF EXTERIOR WALLS, CORRIDOR WALLS & INTERIOR WALLS. UNO.
2. DIMENSIONS ARE TO CENTERLINE OF DEMISING WALLS. UNO.
3. ALL EXPOSED STRUCTURAL STEEL TO RECEIVE 1R INTRINSIC PAINTING. UNO.
4. AT FRAMED EXTERIOR WALLS, FRAMING TO BE SET BACK 5/8" FROM FACE OF CONCRETE TO ALLOW FOR FLUSH ALIGNMENT OF SHEATHING TO EDGE OF CONCRETE SLAB. UNO.
5. CASEWORK DIMENSIONS ARE TO FACE OF FINISH. UNO.
6. SEE SHEETS A0 10 AND A0 11 FOR ASSEMBLIES.
7. ALL CORRIDOR WALLS ARE TYPE **E6**. UNO.
8. ALL DEMISING WALLS ARE TYPE **J6**. UNO.
9. ALL INTERIOR PARTITIONS ARE TYPE **A6**. UNO.
10. ALL FURRING ABOVE CONCRETE STRUCTURAL COLUMNS TYPE **G1**. UNO.
11. ALL VENT SHAWT WALLS ARE TYPE **K4**. UNO.
12. REFER TO LIFE SAFETY PLANS A0 30 - A0 34 FOR FULL EXTENT OF FIRE RATED WALLS.
13. UNIT PLAN LAYOUTS ON SHEETS A2 A4 - A2 A8.
14. ALL OWNER PARTITIONS SHALL INCLUDE ELEVATOR MECHANICAL EQUIPMENT ENCLOSURE.
15. REFER TO SHEET A0 08 FOR ANSI TYPE B ACCESSIBILITY REQUIREMENTS.
16. REFER TO SHEET A0 07 FOR ANSI TYPE A ACCESSIBILITY REQUIREMENTS.
17. REFER TO SHEET A0 04 FOR ADA PUBLIC SPACE ACCESSIBILITY REQUIREMENTS.
18. MECHANICAL EQUIPMENT ENCLOSURES SHALL INCLUDE ELEVATOR MECHANICAL EQUIPMENT ENCLOSURE.
19. CONTRACTOR TO COORDINATE WITH FLOOR PLAC MANUFACTURER GUIDELINES FOR VENTING.

