

SECTION 12 3661

SIMULATED STONE COUNTERTOPS

PART 1 GENERAL

1.1 SUMMARY

- A. Work of this Section includes but is not limited to the following:
 - 1. Solid-surface-material countertops and backsplashes.
- B. Related Documents and Sections: Examine Contract Documents for requirements that directly affect or are affected by Work of this Section. Other Documents and Sections that directly relate to work of this Section include, but are not limited to:
 - 1. Drawings and general provisions of the Contract, including General and Supplementary Conditions, and Division 01 General Requirements Specification Sections.
 - 2. Section 06 4000 - INTERIOR ARCHITECTURAL WOODWORK.
 - 3. Section 12 3530 - RESIDENTIAL CASEWORK.
 - 4. Division 22, PLUMBING.

1.2 SUBMITTALS

- A. Product Data: For countertop materials.
- B. Shop Drawings: For countertops. Show materials, finishes, edge and backsplash profiles, methods of joining, and cutouts for plumbing fixtures.
- C. Samples: For the following products:
 - 1. Countertop material, 6 inches square.

1.3 QUALITY ASSURANCE

- A. Qualifications:
 - 1. Manufacturer Qualifications: A firm experienced a minimum five (5) years in manufacturing products or systems similar to those indicated for this Project and with a record of successful in-service performance.
 - 2. Installer Qualifications: Perform installation with skilled, experienced and trained workmen supervised by trained personnel who shall have at least three (3) years successful experience in installations of similar size and scope.

1.4 PROJECT CONDITIONS

- A. Field Measurements: Verify dimensions of countertops by field measurements after base cabinets are installed but before countertop fabrication is complete.

1.5 COORDINATION

- A. Coordinate locations of utilities that will penetrate countertops or backsplashes.

PART 2 PRODUCTS

2.1 QUARTZ AGGLOMERATE COUNTERTOPS

- A. Quartz Agglomerate: Solid sheets consisting of quartz aggregates bound together with a matrix of filled plastic resin and complying with the "Physical Characteristics of Materials" Article of ANSI SS1.
 - 1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - a. Basis-of-Design Manufacturer: Caesarstone.
 - b. Celador by Stone Source.
 - c. Cosentino USA.
 - d. Technistone USA, Inc.
 - 2. Colors and Patterns: Refer to Section 09 0600.
- B. Countertops: 3/4-inch- (19-mm-) thick, quartz agglomerate with front edge built up with same material.

2.2 FABRICATION

- A. Fabrication: Fabricate tops in one piece with shop-applied edges unless otherwise indicated. Comply with quartz agglomerate manufacturer's written instructions for adhesives, sealers, fabrication, and finishing.

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install countertops level to a tolerance of 1/8 inch in 8 feet.
- B. Fasten countertops by screwing through corner blocks of base units into underside of countertop. Pre-drill holes for screws as recommended by manufacturer. Align adjacent surfaces and, using adhesive in color to match countertop, form seams to comply with manufacturer's written instructions. Carefully dress joints smooth, remove surface scratches, and clean entire surface.
 - 1. Install backsplashes and endsplashes to comply with manufacturer's written instructions for adhesives, sealers, fabrication, and finishing.
 - a. Secure backsplashes to tops with concealed metal brackets at 16 inches o.c. and to walls with adhesive.
 - 2. Seal edges of cutouts in particleboard subtops by saturating with varnish.
 - 3. Align adjacent solid-surfacing-material countertops and form seams to comply with manufacturer's written recommendations using adhesive in color to match countertop. Carefully dress joints smooth, remove surface scratches, and clean entire surface.
 - 4. Calk space between backsplash and wall with sealant specified in Section 07 9200 - JOINT SEALANTS.

END OF SECTION